Model No. VS13518

VX2450wm-LED

60cm/23.6" LED DISPLAY

GO LED GO GREEN

- **Full HD 1080p performance for unsurpassed HD viewing**
- **Impressive 20,000,000:1 dynamic contrast ratio provides greater detail and definition**
  Provides darker black levels and better overall front-of-screen performance.
- **High brightness and 20,000,000 DCR to reflect the true colour**
  300 nits high brightness delivers precise accurate colour to realistically display a full array of brilliant shades and hues.
- **GO LED GO GREEN, EPEAT Silver Certified**
  The VX2450wm-LED has extended gamut with more vibrant colours, while Energy Star compliance, mercury-free RoHS production process, the latest Epeat Silver recognition and WEEE recycling specifications cover the entire product lifecycle for energy saving and contribution to environmental friendliness.
- **Eco-mode automatically reduces power consumption and can extend backlight life and reduce operating power consumption by up to 40%**
- **Windows® 7 certified**

Model Name		VX2450wm-LED
LCD	Size	60cm/23.6" wide Color a-Si TFT Active Matrix LCD with 16:9 aspect ratio
	Optimum Resolution	1920×1080
	Brightness (cd/m²)	300 (typical)
	Contrast Ratio (typical)	1000:1
	Dynamic Contrast Ratio	20,000,000:1
	Viewing Angle (CR≧10 / CR≧5)	170° (H), 160° (V)
	Response Time (ms)	5 (typical)
	Pixel Pitch (H×V)	0.2715 mm (H) x 0.2715mm (V)
	Panel Surface	Anti-Glare, Hard coating (3H)
	Light Source (Hours)	30,000 (typical)
	Colour Support (Millions of colours)	16.7 Millions
INPUT	Analogue	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p)
	Sync	Separate Sync / Composite Sync / SOG
	Frequency (Fh / Fv)	24–83kHz / 50–76Hz
COMPATIBILITY	PC	VGA up to 1920×1080 Non Interlaced
	Mac	1920×1080 Non Interlaced
CONNECTOR	Analogue	1×15 pin mini D-sub
	Digital	1×DVI-D (support HDMI 1.3 and Display Port 1.1 with suitable adaptor)
	Audio	1x3.5mm jack
	Power	Built-in power Adapter, 3-Pin plug
SPEAKER	Speaker	2.5w x 2
POWER	Voltage	AC 100-240V (Universal); 50/60Hz(Switch)
	Consumption (W)	28W (maximum)
	Save mode (W)	≦0.1W
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView / OSD	Auto Image Adjust, Contrast/Brightness, Input Select, D-SUB, DVI, Audio Adjust Volume mute, Colour Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Colour [R, G, B], Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, ECO Mode, Setup Menu Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Memory Recall
OPERATING CONDITIONS	Temperature	0 - 40 (°C) / 32 - 104 (°F)
	Humidity (Non condensed)	10 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	566.22 mm (W) x 443.22 mm (H)x214.48 mm (D)
WEIGHT	Net (w/ stand)	4.5kg (9.92lbs)
REGULATIONS		BSMI, CCC, PSB, C-Tick, KC, e-standby, CE, Ergo, Gost-R / Hygienic, Ukraine, SASO, UL/cUL, FCC-B, ICES-B, TUV-S / UL-AR S Mark, NOM, WEEE, RoHS, Epeat Silver, TCO 5.0
WALL MOUNT (mm)	VESA® Mount Compliant	100 × 100

For more product information, visit us at www.viewsoniceurope.com
VSE 2010/06/29 V3

ViewSonic® See the difference™